

阀插头 VALVE PLUG



单端预铸线束
With open ended wires

BI 型 Form
针距 :11mm Pin spacing
工业标准 Industrial standard



1	型号 Form No.	911001	911021	911041	911061	911081										
电压 Suppression		24V AC/DC 带 LED	24V AC/DC 带 LED 和抑制电路 LED and suppression	110V AC/DC 带 LED 和抑制电路 LED and suppression	0-230V AC/DC 无电路 without electronics	24V AC/DC 带 LED 和抑制电路 LED and suppression										
电路图 Circuit diagram																
针脚排序 Contact layout		PE 与电缆出线同侧 PE side with cable wire 			PE 与电缆出线同侧 PE side with cable wire 											
2	电缆类型 Cable type	护套颜色 Jacket color														
	芯线直径 Wire 0.75mm ²	黄 YE	灰 GY	黑 BK	黄 YE	灰 GY	黑 BK	黄 YE	灰 GY	黑 BK	黄 YE	灰 GY	黑 BK	黄 YE	灰 GY	黑 BK
	PVC	016	216	616	016	216	616	016	216	616	016	216	616	016	216	616
	PUR	026	226	626	026	226	626	026	226	626	026	226	626	026	226	626
	PUR 高柔性 Highly flexible	036	236	636	036	236	636	036	236	636	036	236	636	036	236	636
3	电缆长度 Cable length															
	1.5m	0150														
	3.0m	0300														
	5.0m	0500														
	7.5m	0750														
	10.0m	1000														
	订货号 / Part No.															
	可参考: 1.0.1 Reference: 1.0.1	— — — — — — — — — — — — — — —														
		1 型号 Form				2 电缆类型 Cable type				3 电缆长度 Cable length						
	备注 Notes	技术参数页面 Technical data in chapter: 1.0.7 配件页面 Accessories on page: 1.2.46 不同的电缆长度可根据实际需要, 在订货号的第三部分自行修改, 电缆长度单位: cm														