

# 阀插头 VALVE PLUG

双端预铸线束  
Connection cable  
电磁阀插头 -M12  
Valve plug - M12

BI 型 Form  
针距 :11mm Pin spacing  
工业标准 Industrial standard

插针 Male  
直出线 Straight



<b>1</b>	<b>型号 Form No.</b>	<b>940961</b>	<b>940962</b>				
	<b>电压 Suppression</b>	M12, 3-pole, 24V AC/DC 带 LED 和抑制电路 LED and suppression	M12, 3-pole, 24V AC/DC 带 LED 和抑制电路 LED and suppression				
	<b>电路图 Circuit diagram</b>						
	<b>针脚排序 Contact layout</b>	<p>PE 与电缆出线同侧 PE side with cable wire</p> <p>插孔 Female</p> <p>插针 Male</p>	<p>PE 与电缆出线同侧 PE side with cable wire</p> <p>插孔 Female</p> <p>插针 Male</p>				
<b>2</b>	<b>电缆类型 Cable type</b>	<b>护套颜色 Jacket color</b>					
	芯线直径 Wire 0.75mm <sup>2</sup>	黄 YE	灰 GY	黑 BK	黄 YE	灰 GY	黑 BK
	PVC	016	216	616	016	216	616
	PUR	026	226	626	026	226	626
	PUR 高柔性 Highly flexible	036	236	636	036	236	636
<b>3</b>	<b>电缆长度 Cable length</b>						
	0.3m	0030					
	0.6m	0060					
	1.0m	0100					
	1.5m	0150					
	2.0m	0200					
	<b>订货号 Part No.</b>						
	可参考: 1.0.1 Reference: 1.0.1						
		<b>1</b> 型号 Form	<b>2</b> 电缆类型 Cable type	<b>3</b> 电缆长度 Cable length			
	<b>备注 Notes</b>	技术参数页面 Technical data in chapter: 1.0.7      配件页面 Accessories on page: 1.2.46 不同的电缆长度可根据实际需要, 在订货号的第三部分自行修改, 电缆长度单位: cm					