


大电流 HIGH CURRENT PLUG AND SOCKET



电流极数
Current pole number

400V
50-60Hz
4pole 5pole
6h 6h

Image	A	P	订货号	Diagram	电流 Current				
					16A		32A		
					极数 Pole	4	5	4	5
	16	4	6016411		a	58	64	77	85
	16	5	6016511		b	151	155	77	75
	32	4	6032411		c	16	16	62	60
	32	5	6032511		d	79	85	62	60
	IP67 防溅保护, 暗装直式插座。 IP67 anti-splash protection, dark installed straight socket.					e	5.5	5.5	5.5
					f	8	8	8	8
					h	32	32	32	38
					i	57	57	63	68
					k	84	94	101	164
					l	51	53	58	61
					m	11	13	6	9
					最小导线截面 mm ² Min conducting wire section mm ²	1.5	1.5	2.5	2.5
					最大导线截面 mm ² Max conducting wire section mm ²	4	4	10	10
	63	4	6063411		a	101	101	120	120
	63	5	6063511		b	101	101	120	120
	125	4	6125411		c	82	82	100.5	100.5
	125	5	6125511		d	82	82	100.5	100.5
	IP67 防溅保护, 暗装直式插座。 IP67 anti-splash protection, dark installed straight socket.					e	7	7	7
					f	11	11	12	12
					h	37	37	44.5	44.5
					i	100	100	107	107
					k	112	112	123.5	123.5
					l	72.5	72.5	83	83
					m	10	10	6	6
					最小导线截面 mm ² Min conducting wire section mm ²	6	6	6	6
					最大导线截面 mm ² Max conducting wire section mm ²	16	16	25	25
	16	4	6016421		a	58	64	77	85
	16	5	6016521		b	151	155	77	75
	32	4	6032421		c	16	16	62	60
	32	5	6032521		d	79	85	62	60
	IP67 防溅保护, 暗装直式插座。 IP67 anti-splash protection, dark installed straight socket.					e	5.5	5.5	5.5
					f	8	8	8	8
					h	32	32	32	38
					i	57	57	63	68
					k	84	94	101	164
					l	51	53	58	61
					m	11	13	6	9
					最小导线截面 mm ² Min conducting wire section mm ²	1.5	1.5	2.5	2.5
					最大导线截面 mm ² Max conducting wire section mm ²	4	4	10	10
	63	4	6063421		a	114	114	130	130
	63	5	6063521		b	102	102	120	120
	125	4	6125421		c	89.5	89.5	108.5	108.5
	125	5	6125521		d	81.5	81.5	100.5	100.5
	IP67 防溅保护, 暗装直式插座。 IP67 anti-splash protection, dark installed straight socket.					e	7	7	8
					f	12	12	12.5	12.5
					h	73	73	98	98
					i	80	80	90	90
					l	86	86	95	95
					最小导线截面 mm ² Min conducting wire section mm ²	6	6	6	6
					最大导线截面 mm ² Max conducting wire section mm ²	16	16	25	25