

# KEL 电缆引入系统 CABLE ENTRY SYSTEMS

## KEL 16 可开式穿墙板



可分开穿芯 Split inserts



框架型号 Type	示意图 Description	KT 模块数量 Inserts 小 small / 大 large
KEL 16/8 框架订货号 Part No. 99042168 模块规格见 8.3.8-8.3.9 页 See page 8.3.8-8.3.9 module specifications		8 / -
KEL 16/5 框架订货号 Part No. 99042165 模块规格见 8.3.8-8.3.9 页 See page 8.3.8-8.3.9 module specifications		4 / 1
KEL 16/4 框架订货号 Part No. 99042164 模块规格见 8.3.8-8.3.9 页 See page 8.3.8-8.3.9 module specifications		4 / -
KEL 16/2 框架订货号 Part No. 99042162 模块规格见 8.3.8-8.3.9 页 See page 8.3.8-8.3.9 module specifications		- / 2

材料 Material: 聚酰胺 Polyamide (PA)  
 阻燃等级 Flame class: UL94-V0, 自熄灭 Self-extinguishing  
 防护等级 Protection degree: IP54, 使用密封垫且正确选择穿芯规格  
 (符合 DIN EN 60529:2000-09)  
 With gasket and correct selection of  
 the cable inserts  
 温度范围 Temperature: -40°C to +140°C (静态 Static)  
 特性 Properties: 无卤, 无硅 Halogen-free, silicone-free  
 开孔尺寸 Cut-out dimensions: 37 × 85 mm  
 KEL 高度 Height: 17 mm

开孔尺寸 Platemounting dimensions

