

## KEL-NRG 标准波纹管



型号 Type	订货号 Patr No.	线径 Clamping range
KTF 00	99040000	盲孔穿芯 Blind Insert
KTF 34	99043400	33 - 36 mm
KTF 42	99044200	41 - 44 mm
KTF 54	99045400	53 - 56 mm

材料 Material: 合成橡胶 Elastomer  
 阻燃等级 Flame class: UL94-V0, 自熄灭 Self-extinguishing  
 防护等级 Protection degree: IP54  
 温度范围 Temperature: - 40°C to + 90°C (静态 Static)  
 特性 Properties: 无卤, 无硅 Halogen-free, silicone-free



# KEL 电缆引入系统 CABLE ENTRY SYSTEMS

## KTD 模块 (大) Inserts, large



示意图 Description	型号 Type	订货号 Part No. 灰色 Grey	夹紧范围 Clamping range
KTD (大) – 适用于 KEL64 系列	KTD 35	99046435	35-36 mm
	KTD 36	99046436	36-37 mm
	KTD 37	99046437	37-38 mm
	KTD 38	99046438	38-39 mm
	KTD 39	99046439	39-40 mm
	KTD 40	99046440	40-41 mm
	KTD 41	99046441	41-42 mm
	KTD 42	99046442	42-43 mm
	KTD 43	99046443	43-44 mm
	KTD 44	99046444	44-45 mm
	KTD 45	99046445	45-46 mm
	KTD 46	99046446	46-47 mm
	KTD 47	99046447	47-48 mm
	KTD 48	99046448	48-49 mm
	KTD 49	99046449	49-50 mm
	KTD 50	99046450	50-51 mm
	KTD 51	99046451	51-52 mm
	KTD 52	99046452	52-53 mm
KTD 53	99046453	53-54 mm	
KTD 54	99046454	54-55 mm	
KTD 55	99046455	55-56 mm	
KTD 56	99046456	56-57 mm	



材料 Material: 合成橡胶 Elastomer  
 阻燃等级 Flame class: UL94-V0, 自熄灭 Self-extinguishing  
 防护等级 Protection degree: IP65  
 温度范围 Temperature: -40°C to +90°C (静态 Static)  
 特性 Properties: 无卤, 无硅 Halogen-free, silicone-free