

# 电缆旋紧件及各类电缆附件 CABLE FITTINGS AND ACCESSORIES

PG 制螺纹和 M 制螺纹转换对照图示  
Cross Reference from PG thread to Metric thread

PG制	转换对照表 Cross Reference	M制 Metric
PG11		M20
PG13.5		M20
PG16		M25
PG21		M32
PG29		M40
PG36		M40
PG42		M50
PG48		M50

PG 制电缆接头安装开孔尺寸：  
Mounting dimensions

PG 制螺纹型号	安装开孔尺寸 $D_0^{+0.1}$
PG7	12.8
PG9	15.5
PG11	18.9
PG13.5	20.7
PG16	22.8
PG21	28.6
PG29	37.3
PG36	47.3
PG42	54.3
PG48	59.6

名称 Identification	尺寸 (AG) Designation	夹线范围 $\Phi$ Clamping range (mm)	型号 Type	订货号 Part No.
公制螺纹金属接头 Cable glands, brass nicked-plated    	PG7	2~5 3~6.5	SVL-7-MST SVL-7-MS	60107111 60107101
	PG9	2~6 4~8	SVL-9-MST SVL-9-MS	60109111 60109101
	PG11	3~7 5~10	SVL-11-MST SVL-11-MS	60111111 60111101
	PG13.5	5~9 6~12	SVL-13-MST SVL-13-MS	60113111 60113101
	PG16	7~12 10~14	SVL-16-MST SVL-16-MS	60116111 60116101
	PG21	9~16 13~18	SVL-21-MST SVL-21-MS	60121111 60121101
	PG29	13~20 18~25	SVL-29-MST SVL-29-MS	60129111 60129101
	PG36	20~26 22~32	SVL-36-MST SVL-36-MS	60136111 60136101
	PG42	25~31 32~38	SVL-42-MST SVL-42-MS	60142111 60142101
	PG48	29~35 37~44	SVL-48-MST SVL-48-MS	60148111 60148101
	M12×1.5	2~5 3~6.5	SVL-12-MT SVL-12-M	60112112 60112102
	M16×1.5	2~6 4~8	SVL-16-MT SVL-16-M	60116112 60116102
	M20×1.5	5~9 6~12	SVL-20-MT SVL-20-M	60120112 60120102
	M25×1.5	9~16 13~18	SVL-25-MT SVL-25-M	60125112 60125102
	M32×1.5	13~20 18~25	SVL-32-MT SVL-32-M	60132112 60132102
	M40×1.5	20~26 22~32	SVL-40-MT SVL-40-M	60140112 60140102
	M50×1.5	25~31 32~38	SVL-50-MT SVL-50-M	60150112 60150102
	M63×1.5	29~35 37~44	SVL-63-MT SVL-63-M	60163112 60163102

防护等级 Protection degree: IP68  
 材料 Material: 黄铜镀镍 Nickel plated brass  
 夹紧件 Press seal material: 尼龙 PA  
 密封件 Seal material: NBR  
 工作温度 Temperature range: -40℃ ~ +100℃