

# M12 分配器 DISTRIBUTION SYSTEMS

现场接线插头  
Field-wireable connection cap  
带线插头  
Pre-wired with  
预制线螺丝压接线端子  
Screw plug-in terminals



<b>4 端口 Way</b>	No. ( 单通道 for 1 signal per port )	No. ( 双通道 for 2 signal per port )	No. ( 双通道 for 2 signal per port )
电缆类型 Cable type	PUR/PVC	PUR/PVC	PUR(UL/CSA) 无卤拖链电缆 halogen free
3.0 m	984459-333-0300	984559-362-0300	984559-448-0300
5.0 m	984459-333-0500	984559-362-0500	984559-448-0500
10.0m	984459-333-1000	984559-362-1000	984559-448-1000
15.0m	984459-333-1500	984559-362-1500	984559-448-1500
线径 Wire diameter	4 × 0.34+3 × 0.75mm <sup>2</sup>	8 × 0.34+3 × 0.75mm <sup>2</sup>	8 × 0.5+3 × 1.0mm <sup>2</sup>
电缆 Cable NO.	333	362	448
<b>8 端口 Way</b>	No. ( 单通道 for 1 signal per port )	No. ( 双通道 for 2 signal per port )	No. ( 双通道 for 2 signal per port )
电缆类型 Cable type	PUR/PVC	PUR/PVC	PUR(UL/CSA) 无卤拖链电缆 halogen free
3.0 m	988459-362-0300	988559-398-0300	988559-452-0300
5.0 m	988459-362-0500	988559-398-0500	988559-452-0500
10.0m	988459-362-1000	988559-398-1000	988559-452-1000
15.0m	988459-362-1500	988559-398-1500	988559-452-1500
线径 Wire diameter	8 × 0.34+3 × 0.75mm <sup>2</sup>	16 × 0.34+3 × 0.75mm <sup>2</sup>	16 × 0.5+3 × 1.0mm <sup>2</sup>
电缆 Cable NO.	362	398	452
<b>4 端口 Way</b>	No. ( 双电源 Dual power supply )		
电缆类型 Cable type	PUR/PVC		
3.0 m	984559-374-0300		
5.0 m	984559-374-0500		
10.0m	984559-374-1000		
15.0m	984559-374-1500		
线径 Wire diameter	8 × 0.34+5 × 0.75mm <sup>2</sup>		
电缆 Cable NO.	374		
<b>8 端口 Way</b>	No. ( 双电源 Dual power supply )		
电缆类型 Cable type	PUR/PVC		
3.0 m	988559-403-0300		
5.0 m	988559-403-0500		
10.0m	988559-403-1000		
15.0m	988559-403-1500		
线径 Wire diameter	16 × 0.34+5 × 0.75mm <sup>2</sup>		
电缆 Cable NO.	403		
<b>无电缆 Without cable</b>	No.		
螺丝插入式接线端口 With screw plug-in terminals	988559		
插头适用电缆直径 Plug for cable diameter	8.5…14.0mm		

## 备注 Notes

技术参数页面 Technical data in chapter: 1.0.7      配件页面 Accessories on page: 4.2.18  
不同的电缆长度可根据实际需要，在订货号的第三部分自行修改，电缆长度单位：cm