

# M23 连接器 ROUND PLUG CONNECTOR

现场接线  
Field-wireable

M23 圆形连接器 Round plug connector (9,12)-pole  
插孔 Female 90°



M23 信号连接器

<b>1</b>	<b>型号 Form</b>	<b>No.</b>	<b>923193</b>	<b>923196</b>	<b>923194</b>	<b>923198</b>	<b>923221</b>	<b>923222</b>													
	极数 Suppression		9xØ1mm 9-pole	8x1mm+1x2mm 9-pole	9xØ1mm 9-pole	8x1mm+1x2mm 9-pole	12xØ1mm 12-pole	12xØ1mm 12-pole													
	尺寸图 Description																				
	压线范围 Wire diameter	7-14mm																			
	针脚排序 Contact layout	<p>插孔 Female 逆时针 counterclockwise</p>	<p>插孔 Female 逆时针 counterclockwise</p>	<p>插孔 Female 顺时针 clockwise</p>	<p>插孔 Female 顺时针 clockwise</p>	<p>插孔 Female 逆时针 counterclockwise</p>	<p>插孔 Female 顺时针 clockwise</p>														
<b>2</b>	<b>技术参数 Technical data</b>																				
	额定电压 Supply voltage	160 V AC/DC																			
	额定电流 Current per contact	10A																			
	防护等级 Protection	IP67- 插孔插针配合拧紧 When plugged and screwd down																			
	温度范围 Temperature range	-20...+130°C																			
	测试电压 (两插针之间) Test voltage	2500V																			
	外壳材料 Housing material	锌合金压铸件 黄铜, 镀镍 Zinc alloy die casting Brass, nickel plating																			
	绝缘内嵌体材料 Insulation embedded body material	PA66/PBT, UL 94/V0																			
	接触件 (插孔) Contact element (female)	<p>Ø1mm</p>	<p>Ø2mm</p>	<table border="1"> <thead> <tr> <th>类型 Type</th> <th>压线范围 Wire diameter</th> <th>订货号 Part No.</th> </tr> </thead> <tbody> <tr> <td rowspan="2">插孔 Female Ø1mm</td> <td>0.03-0.34mm<sup>2</sup></td> <td>916201</td> </tr> <tr> <td>0.14-1.00mm<sup>2</sup></td> <td>916221</td> </tr> <tr> <td rowspan="2">插孔 Female Ø2mm</td> <td>0.50-1.50mm<sup>2</sup></td> <td>916231</td> </tr> <tr> <td>0.50-1.50mm<sup>2</sup></td> <td>956221</td> </tr> </tbody> </table>	类型 Type	压线范围 Wire diameter	订货号 Part No.	插孔 Female Ø1mm	0.03-0.34mm <sup>2</sup>	916201	0.14-1.00mm <sup>2</sup>	916221	插孔 Female Ø2mm	0.50-1.50mm <sup>2</sup>	916231	0.50-1.50mm <sup>2</sup>	956221				
类型 Type	压线范围 Wire diameter	订货号 Part No.																			
插孔 Female Ø1mm	0.03-0.34mm <sup>2</sup>	916201																			
	0.14-1.00mm <sup>2</sup>	916221																			
插孔 Female Ø2mm	0.50-1.50mm <sup>2</sup>	916231																			
	0.50-1.50mm <sup>2</sup>	956221																			
	订货号 Part No.																				
	可参考: 1.0.1 Reference: 1.0.1																				
	<b>1</b> 型号 Form																				
	备注 Notes																				
	配件及技术参数页面 Accessories and technical page: 5.6.5																				

# M23 连接器 ROUND PLUG CONNECTOR

现场接线  
Field-wireable

M23 圆形连接器 Round plug connector (17,16+3)-pole  
插孔 Female 90°



M23 信号连接器

<b>1</b>	<b>型号 Form</b>	<b>No.</b>	<b>923271</b>	<b>923272</b>	<b>923291</b>	<b>923292</b>																
	<b>极数</b> Suppression		17xØ1mm 17-pole	17xØ1mm 17-pole	16xØ1mm+3xØ1.5mm 19-pole	16xØ1mm+3xØ1.5mm 19-pole																
	<b>尺寸图 Description</b>																					
	<b>压线范围 Wire diameter</b>	7-14mm																				
	<b>针脚排序</b> Contact layout	 插孔 Female 逆时针 counterclockwise	 插孔 Female 顺时针 clockwise	 插孔 Female 逆时针 counterclockwise	 插孔 Female 顺时针 clockwise																	
<b>2</b>	<b>技术参数 Technical data</b>																					
	额定电压 Supply voltage	160 V AC/DC			125 V AC/DC																	
	额定电流 Current per contact	10A																				
	防护等级 Protection	IP67- 插孔插针配合拧紧 When plugged and screwed down																				
	温度范围 Temperature range	-20...+130°C																				
	测试电压 (两插针之间) Test voltage	2500V																				
	外壳材料 Housing material	锌合金压铸件 黄铜, 镀镍 Zinc alloy die casting Brass, nickel plating																				
	绝缘内嵌体材料 Insulation embedded body material	PA66/PBT, UL 94/V0																				
	<b>接触件 (插孔)</b> Contact element (female)	 Ø1mm	<table border="1"> <thead> <tr> <th>类型 Type</th> <th>压线范围 Wire diameter</th> <th>订货号 Part No.</th> </tr> </thead> <tbody> <tr> <td rowspan="2">插孔 Female Ø1mm</td> <td>0.03-0.34mm<sup>2</sup></td> <td>916201</td> </tr> <tr> <td>0.14-1.00mm<sup>2</sup></td> <td>916221</td> </tr> <tr> <td>插孔 Female Ø1.5mm</td> <td>0.50-1.50mm<sup>2</sup></td> <td>916231</td> </tr> <tr> <td rowspan="2">插孔 Female Ø1.5mm</td> <td>0.24-1.00mm<sup>2</sup></td> <td>936201</td> </tr> <tr> <td>0.50-1.50mm<sup>2</sup></td> <td>936221</td> </tr> </tbody> </table>	类型 Type	压线范围 Wire diameter	订货号 Part No.	插孔 Female Ø1mm	0.03-0.34mm <sup>2</sup>	916201	0.14-1.00mm <sup>2</sup>	916221	插孔 Female Ø1.5mm	0.50-1.50mm <sup>2</sup>	916231	插孔 Female Ø1.5mm	0.24-1.00mm <sup>2</sup>	936201	0.50-1.50mm <sup>2</sup>	936221			
类型 Type	压线范围 Wire diameter	订货号 Part No.																				
插孔 Female Ø1mm	0.03-0.34mm <sup>2</sup>	916201																				
	0.14-1.00mm <sup>2</sup>	916221																				
插孔 Female Ø1.5mm	0.50-1.50mm <sup>2</sup>	916231																				
插孔 Female Ø1.5mm	0.24-1.00mm <sup>2</sup>	936201																				
	0.50-1.50mm <sup>2</sup>	936221																				
	<b>订货号 Part No.</b>																					
	可参考: 1.0.1 Reference: 1.0.1																					
	<b>1</b>	<b>型号 Form</b>																				
	<b>备注 Notes</b>	配件及技术参数页面 Accessories and technical page: 5.6.5																				