

M23 连接器 ROUND PLUG CONNECTOR

现场接线
Field-wireable

M23 圆形连接器 Round plug connector (9,12)-pole
插针 Male 90° 法兰安装 Flange installation



1	型号 Form	No.	923491	923495	923492	923497	923421	923422														
	极数 Suppression		9xØ1mm 9-pole	8x1mm+1x2mm 9-pole	9xØ1mm 9-pole	8x1mm+1x2mm 9-pole	12xØ1mm 12-pole	12xØ1mm 12-pole														
	尺寸图 Description	<div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;"> <p>外型尺寸</p> </div> <div style="text-align: center;"> <p>开孔尺寸</p> </div> </div>																				
	针脚排序 Contact layout		<p>插针 Male 逆时针 counterclockwise</p>	<p>插针 Male 逆时针 counterclockwise</p>	<p>插针 Male 顺时针 clockwise</p>	<p>插针 Male 顺时针 clockwise</p>	<p>插针 Male 逆时针 counterclockwise</p>	<p>插针 Male 顺时针 clockwise</p>														
2	技术参数 Technical data																					
	额定电压 Supply voltage	160 V AC/DC																				
	额定电流 Current per contact	10A																				
	防护等级 Protection	IP67- 插孔插针配合拧紧 When plugged and screwed down																				
	温度范围 Temperature range	-20...+130°C																				
	测试电压 (两插针之间) Test voltage	2500V																				
	外壳材料 Housing material	锌合金压铸件 黄铜, 镀镍 Zinc alloy die casting Brass, nickel plating																				
	绝缘内嵌体材料 Insulation embedded body material	PA66/PBT, UL 94/V0																				
	接触件 (插针) Contact element (male)	<p>Ø1mm</p>	<table border="1"> <thead> <tr> <th>类型 Type</th> <th>压线范围 Wire diameter</th> <th>订货号 Part No.</th> </tr> </thead> <tbody> <tr> <td rowspan="3">插针 Male Ø1mm</td> <td>0.03-0.34mm²</td> <td>916101</td> </tr> <tr> <td>0.14-1.00mm²</td> <td>916121</td> </tr> <tr> <td>0.50-1.50mm²</td> <td>916131</td> </tr> <tr> <td>插针 Male Ø2mm</td> <td>0.50-1.50mm²</td> <td>956121</td> </tr> </tbody> </table>		类型 Type	压线范围 Wire diameter	订货号 Part No.	插针 Male Ø1mm	0.03-0.34mm ²	916101	0.14-1.00mm ²	916121	0.50-1.50mm ²	916131	插针 Male Ø2mm	0.50-1.50mm ²	956121					
类型 Type	压线范围 Wire diameter	订货号 Part No.																				
插针 Male Ø1mm	0.03-0.34mm ²	916101																				
	0.14-1.00mm ²	916121																				
	0.50-1.50mm ²	916131																				
插针 Male Ø2mm	0.50-1.50mm ²	956121																				
	订货号 Part No.																					
	可参考: 1.0.1 Reference: 1.0.1																					
	1	型号 Form																				
	备注 Notes	配件及技术参数页面 Accessories and technical page: 5.6.5																				

M23 连接器 ROUND PLUG CONNECTOR


现场接线
Field-wireable

M23 圆形连接器 Round plug connector (17,16+3)-pole
插针 Male 90° 法兰安装 Flange installation




1 型号 Form No.	923471	923472	923493	923494
极数 Suppression	17xØ1mm 17-pole	17xØ1mm 17-pole	16xØ1mm+3xØ1.5mm 19-pole	16xØ1mm+3xØ1.5mm 19-pole

尺寸图 Description




外型尺寸



开孔尺寸


针脚排序
Contact layout

插针
Male




逆时针
counterclockwise

插针
Male




顺时针
clockwise

插针
Male



逆时针
counterclockwise

插针
Male



顺时针
clockwise

2 技术参数 Technical data

额定电压 Supply voltage	160 V AC/DC	125 V AC/DC
额定电流 Current per contact	10A	
防护等级 Protection	IP67- 插孔插针配合拧紧 When plugged and screwed down	
温度范围 Temperature range	-20...+130°C	
测试电压 (两插针之间) Test voltage	2500V	
外壳材料 Housing material	锌合金压铸件 黄铜, 镀镍 Zinc alloy die casting Brass, nickel plating	
绝缘内嵌材料 Insulation embedded body material	PA66/PBT, UL 94/V0	

接触件 (插针)
Contact element (male)



Ø1mm



Ø1.5mm

类型 Type	压线范围 Wire diameter	订货号 Part No.
插针 Male Ø1mm	0.03-0.34mm ²	916101
	0.14-1.00mm ²	916121
	0.50-1.50mm ²	916131
插针 Male Ø1.5mm	0.24-1.00mm ²	936101
	0.50-1.50mm ²	936121

订货号 Part No.

可参考: 1.0.1
Reference: 1.0.1

1 型号 Form

备注 Notes

配件及技术参数页面 Accessories and technical page: 5.6.5