

M23 连接器 ROUND PLUG CONNECTOR

现场接线
Field-wireable
6-pole
3+PE+4-pole
3+PE+5-pole

插孔 Female
直出线 straight



插孔 Female
90°



1	型号 Form	No.	923601	923801	923901	923411	923611	923822										
	极数 Suppression		6p(6xØ2)	8p(4xØ2+4xØ1)	9p(4xØ2+5xØ1)	4p(4xØ2)	6p(6xØ2)	8p(4xØ2+4xØ1)										
	尺寸图 Description																	
	压线范围 Wire diameter		7-17mm															
	针脚排序 Contact layout																	
2	技术参数 Technical data		6p(6xØ2)		8p(4xØ2+4xØ1)		9p(4xØ2+5xØ1)											
	额定电压 Supply voltage		630 V AC/DC		630 V (AC/DC) / 250 V (AC/DC)		630 V (AC/DC) / 250 V (AC/DC)											
	额定电流 Current per contact		30A		30A / 10A		30A / 10A											
	防护等级 Protection		IP67- 插孔插针配合拧紧 When plugged and screwd down															
	温度范围 Temperature range		-20...+130°C															
	测试电压 (两插针之间) Test voltage		6000V		6000V / 2500V		6000V / 2500V											
	外壳材料 Housing material		锌合金压铸件 黄铜, 镀镍 Zinc alloy die casting Brass, nickel plating															
	绝缘内嵌体材料 Insulation embedded body material		PA66/PBT, UL 94/V0															
	接触件 (插孔) Contact element (female)		 Ø1mm	<table border="1"> <thead> <tr> <th>类型 Type</th> <th>压线范围 Wire diameter</th> <th>订货号 Part No.</th> </tr> </thead> <tbody> <tr> <td>插孔 Female Ø1mm</td> <td>0.25~1.00mm²</td> <td>916431</td> </tr> <tr> <td rowspan="2">插孔 Female Ø2mm</td> <td>1.00~2.50mm²</td> <td>926201</td> </tr> <tr> <td>2.50~4.00mm²</td> <td>926221</td> </tr> </tbody> </table>		类型 Type	压线范围 Wire diameter	订货号 Part No.	插孔 Female Ø1mm	0.25~1.00mm ²	916431	插孔 Female Ø2mm	1.00~2.50mm ²	926201	2.50~4.00mm ²	926221	 Ø2mm	
类型 Type	压线范围 Wire diameter	订货号 Part No.																
插孔 Female Ø1mm	0.25~1.00mm ²	916431																
插孔 Female Ø2mm	1.00~2.50mm ²	926201																
	2.50~4.00mm ²	926221																
	订货号 Part No.																	
	可参考: 1.0.1 Reference: 1.0.1		-----		-----		-----											
			1 型号 Form															
	备注 Notes		配件及技术参数页面 Accessories and technical page: 5.6.5															

M23 动力连接器