

M23 连接器 ROUND PLUG CONNECTOR

现场接线
Field-wireable
6-pole
3+PE+4-pole
3+PE+5-pole

插针 延长式连接器 Male Extended type connector



1	型号 Form	No.	923661	923881	923991																																																																																			
	极数 Suppression		6p(6xØ2)	8p(4xØ2+4xØ1)	9p(4xØ2+5xØ1)																																																																																			
	尺寸图 Description																																																																																							
	压线范围 Wire diameter	7-17mm																																																																																						
2	针脚排序 Contact layout																																																																																							
<table border="1"> <tr> <td>额定电压 Supply voltage</td> <td colspan="5">630 V (AC/DC) / 250 V (AC/DC)</td> </tr> <tr> <td>额定电流 Current per contact</td> <td colspan="5">30A / 10A</td> </tr> <tr> <td>防护等级 Protection</td> <td colspan="5">IP67- 插孔插针配合拧紧 When plugged and screwed down</td> </tr> <tr> <td>温度范围 Temperature range</td> <td colspan="5">-20...+130°C</td> </tr> <tr> <td>测试电压 (两插针之间) Test voltage</td> <td colspan="5">2500V</td> </tr> <tr> <td>外壳材料 Housing material</td> <td colspan="5">锌合金压铸件 黄铜, 镀镍 Zinc alloy die casting Brass, nickel plating</td> </tr> <tr> <td>绝缘内嵌体材料 Insulation embedded body material</td> <td colspan="5">PA66/PBT, UL 94/V0</td> </tr> <tr> <td>接触件 (插针) Contact element (male)</td> <td> Ø1mm </td> <td> <table border="1"> <tr> <th>类型 Type</th> <th>压线范围 Wire diameter</th> <th>订货号 Part No.</th> </tr> <tr> <td>插针 Male Ø1mm</td> <td>0.25~1.00mm²</td> <td>916331</td> </tr> <tr> <td rowspan="2">插针 Male Ø2mm</td> <td>1.00~2.50mm²</td> <td>926101</td> </tr> <tr> <td>2.50~4.00mm²</td> <td>926121</td> </tr> </table> </td> <td colspan="3"></td> </tr> <tr> <td>订货号 Part No.</td> <td colspan="5"></td> </tr> <tr> <td>可参考: 1.0.1 Reference: 1.0.1</td> <td colspan="5" style="text-align: center;"> </td> </tr> <tr> <td></td> <td colspan="2" style="text-align: center;">1 型号 Form</td> <td colspan="2"></td> <td></td> </tr> <tr> <td>备注 Notes</td> <td colspan="5">配件及技术参数页面 Accessories and technical page: 5.6.5</td> </tr> </table>						额定电压 Supply voltage	630 V (AC/DC) / 250 V (AC/DC)					额定电流 Current per contact	30A / 10A					防护等级 Protection	IP67- 插孔插针配合拧紧 When plugged and screwed down					温度范围 Temperature range	-20...+130°C					测试电压 (两插针之间) Test voltage	2500V					外壳材料 Housing material	锌合金压铸件 黄铜, 镀镍 Zinc alloy die casting Brass, nickel plating					绝缘内嵌体材料 Insulation embedded body material	PA66/PBT, UL 94/V0					接触件 (插针) Contact element (male)	 Ø1mm	<table border="1"> <tr> <th>类型 Type</th> <th>压线范围 Wire diameter</th> <th>订货号 Part No.</th> </tr> <tr> <td>插针 Male Ø1mm</td> <td>0.25~1.00mm²</td> <td>916331</td> </tr> <tr> <td rowspan="2">插针 Male Ø2mm</td> <td>1.00~2.50mm²</td> <td>926101</td> </tr> <tr> <td>2.50~4.00mm²</td> <td>926121</td> </tr> </table>	类型 Type	压线范围 Wire diameter	订货号 Part No.	插针 Male Ø1mm	0.25~1.00mm ²	916331	插针 Male Ø2mm	1.00~2.50mm ²	926101	2.50~4.00mm ²	926121				订货号 Part No.						可参考: 1.0.1 Reference: 1.0.1							1 型号 Form					备注 Notes	配件及技术参数页面 Accessories and technical page: 5.6.5				
额定电压 Supply voltage	630 V (AC/DC) / 250 V (AC/DC)																																																																																							
额定电流 Current per contact	30A / 10A																																																																																							
防护等级 Protection	IP67- 插孔插针配合拧紧 When plugged and screwed down																																																																																							
温度范围 Temperature range	-20...+130°C																																																																																							
测试电压 (两插针之间) Test voltage	2500V																																																																																							
外壳材料 Housing material	锌合金压铸件 黄铜, 镀镍 Zinc alloy die casting Brass, nickel plating																																																																																							
绝缘内嵌体材料 Insulation embedded body material	PA66/PBT, UL 94/V0																																																																																							
接触件 (插针) Contact element (male)	 Ø1mm	<table border="1"> <tr> <th>类型 Type</th> <th>压线范围 Wire diameter</th> <th>订货号 Part No.</th> </tr> <tr> <td>插针 Male Ø1mm</td> <td>0.25~1.00mm²</td> <td>916331</td> </tr> <tr> <td rowspan="2">插针 Male Ø2mm</td> <td>1.00~2.50mm²</td> <td>926101</td> </tr> <tr> <td>2.50~4.00mm²</td> <td>926121</td> </tr> </table>	类型 Type	压线范围 Wire diameter	订货号 Part No.	插针 Male Ø1mm	0.25~1.00mm ²	916331	插针 Male Ø2mm	1.00~2.50mm ²	926101	2.50~4.00mm ²	926121																																																																											
类型 Type	压线范围 Wire diameter	订货号 Part No.																																																																																						
插针 Male Ø1mm	0.25~1.00mm ²	916331																																																																																						
插针 Male Ø2mm	1.00~2.50mm ²	926101																																																																																						
	2.50~4.00mm ²	926121																																																																																						
订货号 Part No.																																																																																								
可参考: 1.0.1 Reference: 1.0.1																																																																																								
	1 型号 Form																																																																																							
备注 Notes	配件及技术参数页面 Accessories and technical page: 5.6.5																																																																																							

M23 动力连接器