

M40 圆形电源连接器 ROUND THE POWER CONNECTOR

M40 圆形连接器
Round plug connector M40

现场接线
Field-wireable

3+PE+2-pole

3+PE+4-pole

插针 Male
延长式 Extended type connector



1	型号 Form	No.	940611	940811															
	极数 Suppression		6p(4 × Ø3.6+2 × Ø2)	8p(4 × Ø3.6+4 × Ø2)															
	尺寸图 Description																		
	压线范围 Wire diameter		13-28mm																
	针脚排序 Contact layout																		
2	技术参数 Technical data																		
	额定电压 Supply voltage	630 V (AC/DC) / 250 V (AC/DC)																	
	额定电流 Current per contact	75A / 30A																	
	防护等级 Protection	IP67- 插孔插针配合拧紧 When plugged and screwed down																	
	温度范围 Temperature range	-20...+130°C																	
	测试电压 (两插针之间) Test voltage	4000V / 2500V																	
	外壳材料 Housing material	锌合金压铸件 黄铜, 镀镍 Zinc alloy die casting Brass, nickel plating																	
	绝缘内嵌体材料 Insulation embedded body material	PA66/PBT, UL 94/V0																	
	接触件 (插针) Contact element (male)		<table border="1"> <thead> <tr> <th>类型 Type</th> <th>压线范围 Wire diameter</th> <th>订货号 Part No.</th> </tr> </thead> <tbody> <tr> <td rowspan="2">插针 Male Ø2mm</td> <td>1.00-2.50mm²</td> <td>926101</td> </tr> <tr> <td>2.50-4.00mm²</td> <td>926121</td> </tr> <tr> <td rowspan="3">插针 Male Ø3.6mm</td> <td>1.50-4.00mm²</td> <td>936141</td> </tr> <tr> <td>6.00mm²</td> <td>936161</td> </tr> <tr> <td>10.00mm²</td> <td>936181</td> </tr> </tbody> </table>	类型 Type	压线范围 Wire diameter	订货号 Part No.	插针 Male Ø2mm	1.00-2.50mm ²	926101	2.50-4.00mm ²	926121	插针 Male Ø3.6mm	1.50-4.00mm ²	936141	6.00mm ²	936161	10.00mm ²	936181	
类型 Type	压线范围 Wire diameter	订货号 Part No.																	
插针 Male Ø2mm	1.00-2.50mm ²	926101																	
	2.50-4.00mm ²	926121																	
插针 Male Ø3.6mm	1.50-4.00mm ²	936141																	
	6.00mm ²	936161																	
	10.00mm ²	936181																	
	订货号 Part No.																		
	可参考: 1.0.1 Reference: 1.0.1																		
		1	型号 Form																
	备注 Notes	配件及技术参数页面 Accessories and technical page: 5.6.5																	