

M40 伺服线束 SERVO APPLICATIONS

伺服动力延长电缆
Servo connection and extension cables



1 型号 Form No.		940420	940620	940820
极数 Suppression		4-pole	6(4+2)-pole	8(4+2+2)-pole
2 电缆类型 Cable type	芯数 pole x 标称截面 mm ² Number of cores and mm ² per conductor	高柔性电缆 Highly flexible	固定安装电缆 Fixed installation	外径 O.D
动力线缆技术参数 Power cable technical data 符合 UL AWM style 20235 CSA 温度范围 Temperature range 挠曲 Flexing : -40°C to +80°C 静态 Fixed installation : -50°C to +90°C 额定电压 Nominal voltage UL / CSA 1000V VDE 动力线 Supply cores : U ₀ / U 600 / 1000V 控制线 Control cores : U ₀ / U 300 / 500V 电缆结构 Design 镀锡铜丝编织屏蔽 Tinned copper screen braiding 橙色护套 Orange jacket (RAL 2003) 符合 In according with DESINA®	(4x1.5)C	901	902	9.7
	(4x2.5)C	903	904	11.1
	(4x4.0)C	905	906	12.9
	(4x6.0)C	907	908	15.2
	(4x1.5+(2x1.0))C	911	912	11.1
	(4x2.5+(2x1.0))C	913	914	13.6
	(4x4.0+(2x1.0))C	915	916	14.2
	(4x6.0+(2x1.0))C	917	918	16.5
	(4x1.5+2x(2x1.0))C	921	922	12.6
	(4x2.5+2x(2x1.0))C	923	924	14.6
	(4x4.0+2x(2x1.0))C	925	926	16.0
	(4x6.0+2x(2x1.0))C	927	928	19.2
	3 电缆长度 Cable length			
1.5m		0150		
3.0m		0300		
5.0m		0500		
7.5m		0750		
10.0m		1000		
订货号 Part No.				
可参考: 1.0.1 Reference: 1.0.1		----- ----- -----		
		1 型号 Form	2 电缆类型 Cable type	3 电缆长度 Cable length
备注 Notes		电缆参数 Cable parameter: 1.0.7 配件及技术页面 Accessories and technical page: 5.6.5 不同的电缆长度可根据实际需要, 在订货号的第三部分自行修改, 电缆长度单位: cm		

伺服动力电缆