

# 现场总线连接器 PLUG CONNECTORS FOR FIELDBUS TECHNOLOGY

Profibus

M12 单端预铸线束  
With open ended wires M12

屏蔽 B-Coded  
Shielded, B-coded



插针 Male  
直出 Straight

插孔 Female  
直出 Straight

插针 Male  
90°

插孔 Female  
90°



现场总线连接器

<b>1</b>	<b>型号 Form</b>	<b>No.</b>	<b>944001</b>	<b>944021</b>
	极数 Suppression		2-pole	2-pole
	电路图 Circuit diagram			
	针脚排序 Contact layout		插针 Male 	插孔 Female 
<b>2</b>	<b>电缆类型 Cable type</b>	<b>护套颜色 Jacket color</b>		
	芯线 Wire 1x2xØ0.64mm		紫 VT	
	PVC 固定安装 Fixed installation		840	
	PUR 高柔性 Highly flexible		841	
<b>3</b>	<b>电缆长度 Cable length</b>			
	0.3m		0030	
	0.6m		0060	
	1.0m		0100	
	1.5m		0150	
	2.0m		0200	
	订货号 Part No.			
	可参考: 1.0.1 Reference: 1.0.1	_____ - _____ - _____ - _____		
		<b>1</b>	<b>型号 Form</b>	<b>2</b>
			<b>电缆类型 Cable type</b>	<b>3</b>
			<b>电缆长度 Cable length</b>	
	备注 Notes			

电缆参数 Cable parameter: 1.0.7      配件页面 Accessories on page: 1.3.4  
不同的电缆长度可根据实际需要, 在订货号的第三部分自行修改, 电缆长度单位: cm