



CAT.5e

双端预铸线束  
Connection cable

屏蔽 Shielded

插针 Male M12  
直出 Straight

插针 Male M12  
直出 Straight



<b>1</b>	<b>型号 Form No.</b>	<b>944521</b>	
	极数 Suppression	4-pole	
	电路图 Circuit diagram		
	针脚排序 Contact layout		
<b>2</b>	<b>电缆类型 Cable type</b>	<b>护套颜色 Jacket color</b>	
	CAT 5e.	绿 GN	蓝 BU
	移动安装 Flexible installation PVC	795	791
	拖链安装 Highly flexible PUR	797	793
<b>3</b>	<b>电缆长度 Cable length</b>		
	1.5m	0150	
	3.0m	0300	
	5.0m	0500	
	7.5m	0750	
	10.0m	1000	
	<b>技术数据 Technical data</b>		
	工作电压 Supply voltage	30 V AC/DC	
	防护等级 Protection	插好并拧紧后 When plugged and screwed down IP65 & IP67 (EN60529)	IP65 & IP67 (M8) - IP20 (RJ45)
	温度范围 Temperature range	-25...+85°C, 取决于电缆质量	
	温度范围 Temperature range	-25...+85°C, 取决于电缆质量	
	<b>订货号 Part No.</b>		
	可参考: 1.0.1 Reference: 1.0.1		
		<b>1</b> 型号 Form	<b>2</b> 电缆类型 Cable type
			<b>3</b> 电缆长度 Cable length
	<b>备注 Notes</b>		
		电缆参数 Cable parameter: 1.0.7 配件及技术页面 Accessories and technical page: 1.3.29 不同的电缆长度可根据实际需要, 在订货号的第三部分自行修改, 电缆长度单位: cm	

现场总线连接器