

PoE CAT.6_A

X-coded to RJ45

双端线束 Connection cable

屏蔽 Shielded

插针 Male M12
直出 Straight

插针 Male RJ45
压接式接线



1	型号 Form No.	948811			
	极数 Suppression	8-pole			
	电路图 Circuit diagram				
	针脚排序 Contact layout				
2	电缆类型 Cable type	护套颜色 Jacket color			
	拖链安装 Highly flexible PUR	<table border="1"> <tr> <td>绿 GN</td> </tr> <tr> <td>798</td> </tr> </table>		绿 GN	798
绿 GN					
798					
3	电缆长度 Cable length				
	1.5m	0150			
	3.0m	0300			
	5.0m	0500			
	7.5m	0750			
	10.0m	1000			
	技术数据 Technical data				
	工作电压 Supply voltage	30 V AC/DC			
	防护等级 Protection	插好并拧紧后 When plugged and screwed down IP65 & IP67 (EN60529)	IP65 & IP67 (M8) – IP20 (RJ45)		
	温度范围 Temperature range	-25...+85°C, 取决于电缆质量	-25...+85°C, 取决于电缆质量		
	订货号 Part No.				
	可参考: 1.0.1 Reference: 1.0.1				
		1 型号 Form	2 电缆类型 Cable type		
			3 电缆长度 Cable length		
	备注 Notes				
		电缆参数 Cable parameter: 1.0.7 配件页面 Accessories on page: 1.3.29 不同的电缆长度可根据实际需要, 在订货号的第三部分自行修改, 电缆长度单位: cm			