

名称 Identification	尺寸 (AG) Designation	$>\varnothing<$ mm	型号 Type	订货号 Part No.
压紧式电磁屏蔽金属接头 Compression, EMC cable glands  <p>防护等级 Protection degree: IP68                      材料 Material: 黄铜镀镍 Nickel plated brass                      主体 Body: 黄铜镀镍 Nickel plated brass                      密封件 Seal material: TPE                      O-ring 型圈: NBR                      工作温度 Temperature range: <math>-40^{\circ}\text{C}</math> to <math>+100^{\circ}\text{C}</math>                      防护等级 Protection degree: IP68                      特征: 须剪断屏蔽金属层电缆, 通过轴套压紧                      Characteristics: must be cut shielded cable, metal layer through the shaft sleeve pressure</p> 	PG11	5.5-8.5	SEMC-11-ST	62111111
	PG11	8.5-12.0	SEMC-11-S	62111101
	PG13	8.0-11.0	SEMC-13-ST	62113111
	PG13	11.0-14.0	SEMC-13-S	62113101
	PG16	8.0-11.0	SEMC-16-ST	62116111
	PG16	11.0-14.0	SEMC-16-S	62116101
	PG21	13.0-16.0	SEMC-21-ST	62121111
	PG21	16.0-19.0	SEMC-21-S	62121101
	PG29	19.0-23.0	SEMC-29-ST	62129111
	PG29	23.0-25.5	SEMC-29-S	62129101
	PG36	25.0-30.5	SEMC-36-ST	62136111
	PG36	30.5-35.0	SEMC-36-S	62136101
	M12×1.5	4.5-6.0	SEMC-12-MT	62112112
	M12×1.5	6.0-7.5	SEMC-12-M	62112102
	M16×1.5	6.0-8.0	SEMC-16-MT	62116112
	M16×1.5	8.0-10.0	SEMC-16-M	62116102
	M20×1.5	8.0-11.0	SEMC-20-MT	62120112
	M20×1.5	11.0-14.0	SEMC-20-M	62120102
	M25×1.5	13.0-16.0	SEMC-25-MT	62125112
	M25×1.5	16.0-19.0	SEMC-25-M	62125102
	M32×1.5	18.0-21.0	SEMC-32-MT	62132112
	M32×1.5	21.0-25.0	SEMC-32-M	62132102
	M40×1.5	24.0-28.5	SEMC-40-MT	62140112
	M40×1.5	28.5-32.0	SEMC-40-M	62140102
	M50×1.5	33.0-37.0	SEMC-50-MT	62150112
	M50×1.5	37.0-41.0	SEMC-50-M	62150102
	M63×1.5	40.0-46.0	SEMC-63-MT	62163112
	M63×1.5	46.0-50.0	SEMC-63-M	62163102
弹片式电磁屏蔽金属接头 Shrapnel, EMC cable glands  <p>防护等级 Protection degree: IP68                      材料 Material: 黄铜镀镍 Nickel plated brass                      主体 Body: 黄铜镀镍 Nickel plated brass                      密封件 Seal material: TPE                      O-ring 型圈: NBR                      工作温度 Temperature range: <math>-40^{\circ}\text{C}</math> to <math>+100^{\circ}\text{C}</math>                      防护等级 Protection degree: IP68                      特征: 适用于快速安装, 无须剪断屏蔽金属层电缆通过弹片式                      Characteristics: Suitable for fast installation, no cut shielding metal layer by cable spring type</p> 	PG7	4.5-6.0	SEMV-7-ST	62207111
	PG7	6.0-7.5	SEMV-7-S	62207101
	PG9	6.0-8.0	SEMV-9-ST	62209111
	PG9	8.0-10.0	SEMV-9-S	62209101
	PG11	5.5-8.5	SEMV-11-ST	62211111
	PG11	8.5-12.0	SEMV-11-S	62211101
	PG13	8.0-11.0	SEMV-13-ST	62213111
	PG13	11.0-14.0	SEMV-13-S	62213101
	PG16	8.0-11.0	SEMV-16-ST	62216111
	PG16	11.0-14.0	SEMV-16-S	62216101
	PG21	13.0-16.0	SEMV-21-ST	62221111
	PG21	16.0-19.0	SEMV-21-S	62221101
	PG29	19.0-23.0	SEMV-29-ST	62229111
	PG29	23.0-25.5	SEMV-29-S	62229101
	M12×1.5	4.5-6.0	SEMV-12-MT	62212112
	M12×1.5	6.0-7.5	SEMV-12-M	62212102
	M16×1.5	6.0-8.0	SEMV-16-MT	62216112
	M16×1.5	8.0-10.0	SEMV-16-M	62216102
	M20×1.5	8.0-11.0	SEMV-20-MT	62220112
	M20×1.5	11.0-14.0	SEMV-20-M	62220102
	M25×1.5	13.0-16.0	SEMV-25-MT	62225112
	M25×1.5	16.0-19.0	SEMV-25-M	62225102
	M32×1.5	18.0-21.0	SEMV-32-MT	62232112
	M32×1.5	21.0-25.0	SEMV-32-M	62232102
	M40×1.5	20.0-26.0	SEMV-40-MT	62240112
	M40×1.5	22.0-32.0	SEMV-40-M	62240102
	M50×1.5	25.0-31.0	SEMV-50-MT	62250112
	M50×1.5	32.0-38.0	SEMV-50-M	62250102
M63×1.5	29.0-35.0	SEMV-63-MT	62263112	
M63×1.5	37.0-47.0	SEMV-63-M	62263102	