

















M12 圆形连接器 ROUND PLUG CONNECTOR

现场接线
Field-wireable

插针 Male
直出 Straight

插孔 Female
直出 Straight



1 极数 Suppression	4-pole		5-pole		4-pole		5-pole	
	A-Coded 订货号 Part No.							
螺钉压接 With screw terminals	912701	912741	912721	912761	912901	912941	912921	912961
弹片压接 Cage-clamp terminals	912703		912723		912903		912923	
针脚排序 Contact layout								
B-Coded 订货号 Part No.								
螺钉压接 With screw terminals	913093		914002		913703		914003	
弹片压接 Cage-clamp terminals	913393		914302		913733		914303	
针脚排序 Contact layout								
D-Coded 订货号 Part No.								
螺钉压接 With screw terminals	914007				914008			
弹片压接 Cage-clamp terminals	914307				914308			
针脚排序 Contact layout								
压线范围 Wire diameter	4...6 mm	6...8 mm	4...6 mm	6...8 mm	4...6 mm	6...8 mm	4...6 mm	6...8 mm
电路图 Circuit diagram								
2 技术参数 Technical data								
额定电压 Supply voltage	250 V AC/DC		125 V AC/DC		250 V AC/DC		125 V AC/DC	
额定电流 Current per contact (40°C)	max. 4 A							
压线范围 Connection diameter	最大 max. 0.75 mm ²							
外壳材料 Housing material	阻燃塑料 Flame retardant plastic							
防护等级 Protection	IP67- 插孔插针配合拧紧 (EN 60529) When plugged and screwed down							
温度范围 Temperature range	-25...+85°C							
尺寸图 Description								
订货号 Part No.								
可参考: 1.0.1 Reference: 1.0.1	-----		-----		-----		-----	
1 型号 Form								
备注 Notes								
	配件及技术参数页面 Accessories and technical page: 1.2.46							

M12 圆形连接器 ROUND PLUG CONNECTOR

现场接线
Field-wireable

螺钉压接
With screw terminals

插针 Male
直出 Straight



插孔 Female
直出 Straight



1	型号 Form	No. 917301	917321
	极数 Suppression	8-pole	8-pole
	电路图 Circuit diagram		
	压线范围 Wire diameter	6...8 mm	6...8 mm
	针脚排序 Contact layout	<p>插针 Male</p>	<p>插孔 Female</p>
2	技术参数 Technical data		
	额定电压 Supply voltage	60 V AC/DC	
	额定电流 Current per contact (40°C)	max. 2 A	
	压线范围 Connection diameter	最大 max. 0.5 mm ²	
	外壳材料 Housing material	阻燃塑料 Flame retardant plastic	
	压线方式 Wiring method	螺钉压接 Screw terminals	
	防护等级 Protection	IP67- 插孔插针配合拧紧 (EN 60529) When plugged and screwed down	
	温度范围 Temperature range	-25...+85°C	
	尺寸图 Description		
	订货号 Part No.		
	可参考: 1.0.1 Reference: 1.0.1		
	1 型号 Form		
	备注 Notes		
		配件及技术参数页面 Accessories and technical page: 1.2.46	