

M12 圆形连接器 ROUND PLUG CONNECTOR

现场接线
Field-wireable

插针 Male
90°



插孔 Female
90°



1	极数 Suppression	4-pole		5-pole		4-pole		5-pole	
	A-Coded 订货号 Part No.	912821 912861		912841 912881		912981 913021		913001 913041	
螺钉压接 With screw terminals	912821		912843		912983		913003		
弹片压接 Cage-clamp terminals	912823		912843		912983		913003		
针脚排序 Contact layout									
B-Coded 订货号 Part No.	912071		912171		913701		913171		
螺钉压接 With screw terminals	912073		912173		913731		913173		
弹片压接 Cage-clamp terminals	912073		912173		913731		913173		
针脚排序 Contact layout									
D-Coded 订货号 Part No.	914471				914571				
螺钉压接 With screw terminals	914473				914573				
弹片压接 Cage-clamp terminals	914473				914573				
针脚排序 Contact layout									
压线范围 Wire diameter	4...6 mm	6...8 mm	4...6 mm	6...8 mm	4...6 mm	6...8 mm	4...6 mm	6...8 mm	
电路图 Circuit diagram									
2 技术参数 Technical data	250 V AC/DC		125 V AC/DC		250 V AC/DC		125 V AC/DC		
额定电压 Supply voltage	max. 4 A		max. 4 A		max. 4 A		max. 4 A		
额定电流 Current per contact (40°C)	最大 max. 0.75 mm ²		最大 max. 0.75 mm ²		最大 max. 0.75 mm ²		最大 max. 0.75 mm ²		
压线范围 Connection diameter	阻燃塑料 Flame retardant plastic		阻燃塑料 Flame retardant plastic		阻燃塑料 Flame retardant plastic		阻燃塑料 Flame retardant plastic		
外壳材料 Housing material	IP67- 插孔插针配合拧紧 (EN 60529) When plugged and screwed down		IP67- 插孔插针配合拧紧 (EN 60529) When plugged and screwed down		IP67- 插孔插针配合拧紧 (EN 60529) When plugged and screwed down		IP67- 插孔插针配合拧紧 (EN 60529) When plugged and screwed down		
防护等级 Protection	-25...+85°C		-25...+85°C		-25...+85°C		-25...+85°C		
温度范围 Temperature range									
尺寸图 Description									
订货号 Part No.	-----		-----		-----		-----		
可参考: 1.0.1 Reference: 1.0.1	-----		-----		-----		-----		
	1 型号 Form								
备注 Notes	配件及技术参数页面 Accessories and technical page: 1.2.46		配件及技术参数页面 Accessories and technical page: 1.2.46		配件及技术参数页面 Accessories and technical page: 1.2.46		配件及技术参数页面 Accessories and technical page: 1.2.46		

M12 圆形连接器 ROUND PLUG CONNECTOR







现场接线
Field-wireable
螺钉压接
With screw terminals

插针 Male
90°



插孔 Female
90°



1	型号 Form	No.	917311	917331
	极数 Suppression		8-pole	8-pole
	电路图 Circuit diagram			
	压线范围 Wire diameter		6...8 mm	6...8 mm
	针脚排序 Contact layout		<p>插针 Male</p> 	<p>插孔 Female</p> 
2	技术参数 Technical data			
	额定电压 Supply voltage	60 V AC/DC		
	额定电流 Current per contact (40°C)	max. 2 A		
	压线范围 Connection diameter	最大 max. 0.5 mm ²		
	外壳材料 Housing material	阻燃塑料 Flame retardant plastic		
	压线方式 Wiring method	螺钉压接 Screw terminals		
	防护等级 Protection	IP67- 插孔插针配合拧紧 (EN 60529) When plugged and screwed down		
	温度范围 Temperature range	-25...+85°C		
	尺寸图 Description			
	订货号 Part No.			
	可参考: 1.0.1 Reference: 1.0.1	<p>-----</p>		
	1 型号 Form			
	备注 Notes			
		配件及技术参数页面 Accessories and technical page: 1.2.46		