

M12 圆形连接器 ROUND PLUG CONNECTOR

M12 T-coded
现场接线 Field-wireable

插针 Male
直出 Straight



插孔 Female
直出 Straight



| | | | |
|----------|---------------------------------|--|--|
| 1 | 型号 Form | No. 912744 | 912932 |
| | 极数 Suppression | 4-pole | 4-pole |
| | 电路图 Circuit diagram |  |  |
| | 针脚排序 Contact layout | <p>插针 Male</p>  | <p>插孔 Female</p>  |
| 2 | 技术参数 Technical data | | |
| | 额定电压 Supply voltage | 60 V AC/DC | |
| | 额定电流 Current per contact (40°C) | max. 12 A | |
| | 压线范围 Connection diameter | 最大 max. 1.5 mm ² | |
| | 外壳材料 Housing material | 铜锌合金, 表面镀镍 CuZn, nickel plated | |
| | 压线方式 Wiring method | 螺钉压接 Screw terminal | |
| | 防护等级 Protection | IP65 – 插孔插针配合拧紧 (EN 60529) When pluggde and screwed down | |
| | 温度范围 Temperature range | -25...+85°C | |
| | 订货号 Part No. | | |
| | 可参考: 1.0.1 Reference: 1.0.1 |  | |
| | | 1 | 型号 Form |
| | 备注 Notes | | |