

# 板后安装连接器 PLATE CONNECTOR AFTER INSTALLATION

A-Coded  
B-Coded  
D-Coded

带线板后安装  
Pre-wired installation



M12 插针 Male



M12 插孔 Female



1 极数 Suppression	4-pole	5-pole	8-pole	4-pole	5-pole	8-pole
<b>A-Coded</b> 订货号 Part No.	913501	913521	917161	913541	913561	917181
针脚排序 Contact layout						
<b>B-Coded</b> 订货号 Part No.	913502	913522		913542	913562	
针脚排序 Contact layout						
<b>D-Coded</b> 订货号 Part No.	913503			913543		
针脚排序 Contact layout						
<b>2 螺母固定 Suitable mounting nut</b>						
螺母固定 Suitable mounting nut M16 x 1.5	971	972	973	971	972	973
螺母固定 Suitable mounting nut PG9	977	978	979	977	978	979
尺寸图 Description						
订货号 Part No.						
PCB 安装产品订购 只需填写型号 PCB product installation order only need to fill in the model	<div style="display: flex; justify-content: space-around;"> <span>1</span> <span>2</span> <span>3</span> </div>					
备注 / Notes	<p>1 型号 Form      2 电缆类型 Cable type      3 电缆长度 Cable length</p>					

技术参数页面 Technical data in chapter: 1.0.7

不同的电缆长度可根据实际需要, 在订货号的第三部分自行修改, 电缆长度单位: cm

# 板后安装连接器 PLATE CONNECTOR AFTER INSTALLATION

带线板后安装技术参数  
Pre-wired installation

A-Coded  
B-Coded  
D-Coded

M12 插针 Male



M12 插孔 Female



1	极数 Suppression	4-pole	5-pole	8-pole	4-pole	5-pole	8-pole
	<b>A-Coded</b> 订货号 Part No.	913501	913521	917161	913541	913561	917181
	<b>B-Coded</b> 订货号 Part No.	913502	913522		913542	913562	
	<b>D-Coded</b> 订货号 Part No.	913503			913543		
电路图 Circuit diagram	 <p>1 棕 BN 2 白 WH 4 黑 BK 3 蓝 BU</p>	 <p>1 棕 BN 2 白 WH 4 黑 BK 3 蓝 BU 5 灰 GY</p>	 <p>1 白 WH 2 棕 BN 3 绿 GN 4 黄 YE 5 灰 GY 6 粉 PK 7 蓝 BU 8 红 RD</p>	 <p>1 棕 BN 2 白 WH 4 黑 BK 3 蓝 BU</p>	 <p>1 棕 BN 2 白 WH 4 黑 BK 3 蓝 BU 5 灰 GY</p>	 <p>1 白 WH 2 棕 BN 3 绿 GN 4 黄 YE 5 灰 GY 6 粉 PK 7 蓝 BU 8 红 RD</p>	
2	技术参数 Technical data						
	<b>A-Coded</b>						
	额定电压 Supply voltage	250 V AC/DC	125 V AC/DC	60 V AC/DC	250 V AC/DC	125 V AC/DC	60 V AC/DC
	额定电流 Current per contact (40°C)	4A		2A	4A		2A
	防护等级 Protection	IP67- 插孔插针配合拧紧 ( EN 60529 ) When plugged and screwed down					
	导体截面积 Connection diameter	0.25 mm <sup>2</sup>					
	温度范围 Temperature range	- 25...+ 85 °C					
	<b>B-Coded</b>						
	额定电压 Supply voltage	250 V AC/DC	125 V AC/DC		250 V AC/DC	125 V AC/DC	
	额定电流 Current per contact (40°C)	4A					
	防护等级 Protection	IP67- 插孔插针配合拧紧 ( EN 60529 ) When plugged and screwed down					
	导体截面积 Connection diameter	0.25 mm <sup>2</sup>					
	温度范围 Temperature range	- 25...+ 85 °C					
<b>D-Coded</b>							
额定电压 Supply voltage	250 V AC/DC						
额定电流 Current per contact (40°C)	4A						
防护等级 Protection	IP67- 插孔插针配合拧紧 ( EN 60529 ) When plugged and screwed down						
导体截面积 Connection diameter	0.25 mm <sup>2</sup>						
温度范围 Temperature range	- 25...+ 85 °C						