

# 板前安装连接器 BEFORE INSTALL THE CONNECTOR

A-Coded  
B-Coded  
D-Coded

带线板前安装  
Pre-wired installation



M12 插针 Male



M12 插孔 Female



1	极数 Suppression	4-pole	5-pole	8-pole	4-pole	5-pole	8-pole	
	<b>A-Coded</b> 订货号 Part No.	913504	913524	917164	913544	913564	917184	
	针脚排序 Contact layout	插针 Male 	插针 Male 	插针 Male 	插孔 Female 	插孔 Female 	插孔 Female 	
	<b>B-Coded</b> 订货号 Part No.	913505	913525		913545	913565		
	针脚排序 Contact layout	插针 Male 	插针 Male 		插孔 Female 	插孔 Female 		
	<b>D-Coded</b> 订货号 Part No.	913506			913546			
	针脚排序 Contact layout	插针 Male 			插孔 Female 			
2	螺母固定 Suitable mounting nut							
	螺母固定 Suitable mounting nut M16 x 1.5	971	972	973	971	972	973	
	螺母固定 Suitable mounting nut M12 x 1.0	974	975	976	974	975	976	
	螺母固定 Suitable mounting nut PG9	977	978	979	977	978	979	
	尺寸图 Description							
	订货号 Part No.							
	PCB 安装产品订购 只需填写型号 PCB product installation order only need to fill in the model	<div style="display: flex; justify-content: space-around;"> <span>-----</span> <span>-----</span> <span>-----</span> <span>-----</span> <span>-----</span> </div>						
		1 型号 Form		2 电缆类型 Cable type		3 电缆长度 Cable length		
	备注 Notes	技术参数页面 Technical data in chapter: 1.0.7 不同的电缆长度可根据实际需要, 在订货号的第三部分自行修改, 电缆长度单位: cm						

# 板前安装连接器 PLATE CONNECTOR AFTER INSTALLATION

带线板前安装技术参数  
Pre-wired installation

A-Coded  
B-Coded  
D-Coded

M12 插针 Male



M12 插孔 Female



1	极数 Suppression	4-pole	5-pole	8-pole	4-pole	5-pole	8-pole
	<b>A-Coded</b> 订货号 Part No.	913504	913524	917164	913544	913564	917184
	<b>B-Coded</b> 订货号 Part No.	913505	913525		913545	913565	
	<b>D-Coded</b> 订货号 Part No.	913505			913545		
电路图 Circuit diagram	 <p>1 棕 BN 2 白 WH 4 黑 BK 3 蓝 BU</p>	 <p>1 棕 BN 2 白 WH 4 黑 BK 3 蓝 BU 5 灰 GY</p>	 <p>1 白 WH 2 棕 BN 3 绿 GN 4 黄 YE 5 灰 GY 6 粉 PK 7 蓝 BU 8 红 RD</p>	 <p>1 棕 BN 2 白 WH 4 黑 BK 3 蓝 BU</p>	 <p>1 棕 BN 2 白 WH 4 黑 BK 3 蓝 BU 5 灰 GY</p>	 <p>1 白 WH 2 棕 BN 3 绿 GN 4 黄 YE 5 灰 GY 6 粉 PK 7 蓝 BU 8 红 RD</p>	
2	技术参数 Technical data						
<b>A-Coded</b>							
额定电压 Supply voltage	250 V AC/DC	125 V AC/DC	60 V AC/DC	250 V AC/DC	125 V AC/DC	60 V AC/DC	
额定电流 Current per contact (40°C)	4A		2A	4A		2A	
防护等级 Protection	IP67- 插孔插针配合拧紧 ( EN 60529 ) When plugged and screwed down						
导体截面积 Connection diameter	0.25 mm <sup>2</sup>						
温度范围 Temperature range	- 25...+ 85 °C						
<b>B-Coded</b>							
额定电压 Supply voltage	250 V AC/DC	125 V AC/DC		250 V AC/DC	125 V AC/DC		
额定电流 Current per contact (40°C)	4A						
防护等级 Protection	IP67- 插孔插针配合拧紧 ( EN 60529 ) When plugged and screwed down						
导体截面积 Connection diameter	0.25 mm <sup>2</sup>						
温度范围 Temperature range	- 25...+ 85 °C						
<b>D-Coded</b>							
额定电压 Supply voltage	250 V AC/DC						
额定电流 Current per contact (40°C)	4A						
防护等级 Protection	IP67- 插孔插针配合拧紧 ( EN 60529 ) When plugged and screwed down						
导体截面积 Connection diameter	0.25 mm <sup>2</sup>						
温度范围 Temperature range	- 25...+ 85 °C						