

印制电路板安装连接器 PCB CONNECTOR

A-Coded
B-Coded
D-Coded



M12 插针 Male



M12 插孔 Female



1	极数 Suppression	4-pole	5-pole	8-pole	4-pole	5-pole	8-pole		
	A-Coded 订货号 Part No.	913501P	913521P	917161P	913541P	913561P	917181P		
	针脚排序 Contact layout	插针 Male 	插针 Male 	插针 Male 	插孔 Female 	插孔 Female 	插孔 Female 		
	B-Coded 订货号 Part No.	913502P	913522P		913542P	913562P			
	针脚排序 Contact layout	插针 Male 	插针 Male 		插孔 Female 	插孔 Female 			
	D-Coded 订货号 Part No.	913503P			913543P				
	针脚排序 Contact layout	插针 Male 			插孔 Female 				
2	螺母固定 Suitable mounting nut								
	螺母固定 Suitable mounting nut M16 x 1.5	971	972	973	971	972	973		
	螺母固定 Suitable mounting nut PG9	977	978	979	977	978	979		
	尺寸图 Description								
	订货号 Part No.								
	可参考: 1.0.1 Reference: 1.0.1								
		1 型号 Form			2 螺母固定 Cable type				
	备注 Notes								

PCB 安装连接器 INSTALL THE CONNECTOR FOR

A-Coded
B-Coded
D-Coded
90°



M12 插针 Male



M12 插孔 Female



1 极数 Suppression	4-pole	5-pole	4-pole	5-pole
A-Coded 订货号 Part No.	912501	912551	912521	912581
针脚排序 Contact layout	插针 Male 	插针 Male 	插孔 Female 	插孔 Female
B-Coded 订货号 Part No.	912541	912511	912561	912531
针脚排序 Contact layout	插针 Male 	插针 Male 	插孔 Female 	插孔 Female
技术参数 Technical data				
额定电压 Supply voltage	250 V AC/DC	125 V AC/DC	250 V AC/DC	125 V AC/DC
额定电流 Current per contact (40°C)	4A			
防护等级 Protection	IP67-插孔插针配合拧紧(EN 60529) When plugged and screwed down			
拔插寿命(次) Pull out plug life (time)	≥ 100			
温度范围 Temperature range	-25...+85°C			
D-Coded 订货号 Part No.	912571		912591	
针脚排序 Contact layout	插针 Male 		插孔 Female 	
技术参数 Technical data				
额定电压 Supply voltage	250 V AC/DC			
额定电流 Current per contact (40°C)	4A			
防护等级 Protection	IP67-插孔插针配合拧紧(EN 60529) When plugged and screwed down			
拔插寿命(次) Pull out plug life (time)	≥ 100			
温度范围 Temperature range	-25...+85°C			
尺寸图 Description				
	<p>印刷线路板厚度: 1.6MM</p>		<p>印刷线路板厚度: 1.6MM</p>	
	<p>M12板面弯角安装开孔尺寸</p>		<p>M12板面弯角安装开孔尺寸</p>	
备注 Notes				